



- E. L. H. E. R. A. N. O. I. E. S.**
1. FOUNDATION SHALL BE CONSTRUCTED OF 12" WALL AND 18" THICK REINFORCED WITH 3/4" CONTINUOUS BARS WITH #3 CROSS TIES SPACED AT 48" STRS.
 2. CONCRETE BLOCK WALLS ARE SHOWN WITH CONCRETE WALLS ARE SHOWN WITH 4" THICK UNLESS NOTED ARE 4" THICK PLACED OVER A 12" THICK UNLESS NOTED OTHERWISE.
 3. SLAB ON GRADE UNLESS NOTED ARE 4" THICK PLACED OVER A 12" THICK UNLESS NOTED OTHERWISE.
 4. ELEVATIONS ARE SHOWN TO TOPS OF FOOTINGS.
 5. FOUNDATION SHALL VERIFY ALL DIMENSIONS AND CONDITIONS IN THE FIELD.

REVISED: 6-27-74
 SHOWING NEW CORRIDOR BETWEEN BUILDINGS.

BASEMENT FLOOR AND FOUNDATION PLAN	
LOCATION AND NAME OF WORK	ALTERATIONS & ADDITIONS TO EXISTING
CAMBERTA SAVINGS & LOAN ASSN.	1113 N. FRANKLIN ST. PHOENIX, ARIZONA
FRANKLIN STREET JOHNSTOWN, PA.	
NICHOLAS J. FIORE ARCHITECT	
233 BELLE AVE. ALTOONA, PENNSYLVANIA	
PROJECT NO. 434	DATE 5-1-74

BASEMENT FLOOR AND FOUNDATION PLAN
 SCALE: 1/8" = 1'-0"

